

METHODS, SYSTEMS, AND MEDIA TO AUTHENTICATE A USER

FIELD OF INVENTION

5 **[0001]** The present invention is in the field of user authentication. More particularly, the present invention relates to methods, systems, and media to authenticate a user for interaction with applications on a server without requiring the user to repeatedly provide login information like a user name and password.

10 BACKGROUND

[0002] The Internet has seen explosive growth primarily fueled by the introduction and widespread use of web browsers that enable access to networked servers via a simple, graphical, user interface (GUI). Web browsers support hypertext documents, often referred to as web
15 pages, such as hypertext markup language (HTML) and allow a user to load these documents remotely from a server via local area networks (LANs) and wide area networks (WANs).

[0003] Servers like the IBM eServer i-Series and p-Series include a web server application to execute web applications like common gateway interface (CGI) applications in
20 response to requests by a user. More specifically, the web server interacts with the user's web browser to facilitate communication between the server and the user using a hypertext transport protocol (HTTP). The web server passes data between the browser and web applications of the server and finds, loads, and unloads web applications in response to communications from the user via the browser.

25
 [0004] HTTP, however, is a stateless protocol so each request from an HTTP client to an HTTP server is considered a new request and no state is maintained between the requests. Since the most common interactions between a user and a server require multiple, related requests, the server creates a session to track the related requests so the server can react properly to a user's
30 communication. HTTP cookies and/or uniform resource locators (URLs) typically facilitate

tracking of the state of the session on the user's side. Cookies are created by a web application and include data such as a range of URLs for which the cookie is valid. The cookie is then stored on a user's computer via the web browser and returned to the server when the browser encounters the same URLs. URLs can be used in a similar manner by incorporating session data in a URL so a parsing routine can find the session data.

[0005] A session management application on the server typically remains resident in memory, monitoring interactions between a user and the web applications to track the activities of a user via the cookies or URLs. For example, a user may cause a CGI to be executed on the server to perform a product search in a database of an on-line store. When the user causes another CGI to execute to add the results of the product search to a "shopping cart", the session management application creates a session to track items added to the shopping cart.

[0006] When the user decides to check out, the session management application creates a secure session, or login session, to track sensitive information like payment, billing, and shipping information. In particular, by pressing a "checkout" button, the user implements a login CGI that authenticates the user's identity by verifying, e.g., the user's name and password. The session management application must then remember the sensitive information provided by the user to facilitate the checkout process and to avoid the security risks inherent to passing the sensitive information back and forth between the server and web browser via cookies or URLs.

[0007] Current solutions for remembering the login session involve maintaining the session management application resident in memory and storing the sensitive information in memory allocated for the session management application. The session management application can then pass the sensitive information to other applications as necessary to implement the checkout process. Other solutions conserve memory resources in the server by storing the sensitive information in a database application, e.g., on a hard drive. The session management application creates a session identification and transmits a cookie with the session identification to the user for identifying the login session. When the user accesses a web application related to the login session, the cookie is transmitted to the session management application, and the

session management application accesses the database application via an application program interface (API) to verify the user's login information.

[0008] The adaptability associated with such web application architecture has inspired the design of embedded applications for many current servers. In particular, servers such as IBM eServer i-Series and p-Series offer access to system management and configuration applications, referred to as service processor menus, via web browsers. Thus, a user such as an administrator, customer, and/or customer engineer can implement major configuration and system setting changes like managing the boot and shutdown sequences for the server by directing communications to a URL for the embedded system via a web browser.

[0009] Similar to the access of login sessions via web applications, embedded systems may require the user to login and privilege levels associated with the user's login facilitate access to various applications, e.g., service processor menus or functions of the service processor menus. For instance, the customer engineer may have the highest level of access since the function of the customer engineer is typically to identify and repair problems associated with the server. The administrator and customer may have lower privilege levels to provide access to system settings and configurations associated with authorizing and managing users, and customizing the server's functionality for the customer.

[0010] Unlike access to login sessions via web applications, embedded systems do not typically anticipate thousands or hundreds of thousands of concurrent users. Embedded systems may anticipate up to, e.g., a dozen concurrent users, and have relatively limited resources to track user login sessions. Since maintaining the web server, session management application as well as login and session information resident in memory consumes a significant amount of the limited resources available to embedded systems, current solutions are impractical.

[0011] The other solutions that involve maintaining the web server, session management application and session identity resident in memory while storing the sensitive information and session state information within a database application, are slow as well as impractical. In

particular, the session management application must interface with an API for the database application through bridges, secondary busses, and input-output (I/O) drivers to access the sensitive information, compounding the latency involved with each communication that requires user authentication. Further, when considering that only a dozen users may be accessing login sessions concurrently, the use of a database application to store sensitive information is a significant waste of server resources.

SUMMARY OF THE INVENTION

[0012] The problems identified above are in large part addressed by methods, systems, and media to authenticate a user for interaction with applications on a server. One embodiment provides a method for logging a successful authentication of a user. The method generally includes generating a session identification in response to the authentication to identify a login session for the user; storing the session identification in a memory location, the memory location being configured to retain the session identification independent of de-allocations of memory for individual applications, to authenticate the user for at least one of the independent applications; transmitting the session identification to the user; and authenticating the user for the at least one of the independent applications in response to receipt of the session identification upon verifying that the session identification is stored in the memory location.

[0013] Another embodiment provides an apparatus for logging a successful authentication of a user for a server. The apparatus contemplates a memory location to retain a session identification independent of de-allocation of memory for individual applications executed on the server; a session creator coupled with the memory location to generate the session identification in response to the authentication to identify a login session of the user, store the session identification in the memory location, and transmit the session identification to the user; and a session authenticator coupled with the memory location to authenticate the user for an application of the individual applications executed on the server in response to receipt of the session identification upon verifying that the session identification is stored in the memory location.

[0014] A further embodiment provides a machine-accessible medium containing instructions, which when executed by a machine, cause said machine to perform operations. The operations can involve generating a session identification in response to a user authentication via a login application to identify a login session for a user; storing the session identification in a memory location, the allocation for the memory location being independent of allocations of memory to individual applications, to authenticate the user for at least one of the individual applications; transmitting the session identification to the user; and authenticating the user for the at least one of the individual applications in response to receipt of the session identification upon verifying that the session identification is stored in the memory location.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Other objects and advantages of the invention will become apparent upon reading the following detailed description and upon reference to the accompanying drawings in which, like references may indicate similar elements:

FIG 1 depicts an embodiment of a system including an embedded system and user computer coupled via a LAN and/or WAN to authenticate a user for interaction with applications in the embedded system;

FIG 2 depicts an embodiment of an apparatus including a session creator, session authenticator, arbitrator and a shared memory buffer to authenticate a user for interaction with applications;

FIG 3 depicts an example flow chart of a method to authenticate a user for interaction with applications in a server; and

FIG 4 depicts an example flow chart of functionality for a flow chart like the flow chart in FIG 3 to remove user sessions upon expiration or in response to a user activity such as logging out of a session.

DETAILED DESCRIPTION OF EMBODIMENTS

[0016] The following is a detailed description of example embodiments of the invention depicted in the accompanying drawings. The example embodiments are in such detail as to clearly communicate the invention. However, the amount of detail offered is not intended to limit the anticipated variations of embodiments, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the present invention as defined by the appended claims. The detailed descriptions below are designed to make such embodiments obvious to a person of ordinary skill in the art.

[0017] Generally speaking, methods, systems, and media to authenticate a user for interaction with applications in an embedded system of a server are contemplated. Embodiments include hardware and/or software of the embedded system adapted to generate a unique, session identification (ID) like a random number to identify a user and the user's login session. The unique, session ID is stored in a memory location, such as a shared memory buffer, that will not be de-allocated upon termination of applications in the embedded system and is included in a cookie or the like and forwarded to the user's browser or the like so that each time the user executes an application, the user's identification can be verified by locating the corresponding entry in the memory location. Once the user's identification is verified, the user is authorized to access applications associated with the user's secure login session. Such embodiments are thus independent of the architecture of the applications executed by the embedded system. Further embodiments include additional session information with the session ID in the memory location like the user's privilege level, Internet Protocol (IP) address, time stamp, and etc. Some of these embodiments monitor the time stamps or time indications associated with a session ID or logout requests by the user to remove the session ID from the memory location, invalidating accesses with that session ID.

[0018] Turning now to the drawings, FIG 1 depicts an embodiment of a system **100** to authenticate a user. More specifically, system **100** may facilitate a secure login session to an embedded system **110** for a user of a computer like user computer **180** via a wide area network or local area network like WAN/LAN **170**. In many embodiments, embedded system **110** may include one or more processors, or threads of processors, executing code like CGIs and/or one or

more state machines coupled with data storage devices like random access memory (RAM), and files on a hard drive. Upon booting, embedded system **110** may execute a web server **115** to facilitate interaction between a user and web applications **122** like service processor menus to support configuration of and system settings associated with embedded system **110**. Further, when a shared memory buffer, or an application independent area of memory, has not been established, web server **115** may establish a shared memory buffer like shared memory buffer **162** so that data stored by a CGI like a CGI of web applications **122** can be accessed after the CGI unloads or terminates. In other embodiments, the first CGI called by web server **115** may establish a shared memory buffer like shared memory buffer **162**. In further embodiments, the first CGI that attempts to access a shared memory buffer creates a shared memory buffer like shared memory buffer **162**. In still further embodiments, an application that may run prior to executing web server **115** may create a shared memory buffer like shared memory buffer **162**.

[0019] Embedded system **110** may be designed to provide a graphical user interface (GUI) for a user via the user's browser so the user can maintain configurations and settings for boot and shutdown sequences, modify the availability of a processor or processors **150** and memory **160**, update firmware, set passwords, perform diagnostics, and maintain an error log. In the present embodiment, embedded system **110** comprises web server **115**, web applications **122**, a static **135**, a bus **140**, processor(s) **150**, and memory **160**.

[0020] Web server **115** may load and execute a process like a CGI in response to user communication and pass data from the user to the process. When the CGI completes the task, the resulting data is passed back to web server **115**. Then, web server **115** unloads the CGI and passes the resulting data to the user. For instance, upon receiving a request to enter a configuration menu, web server **115** receives a cookie from the user's browser like we browser **185**. Web server locates user session CGI **123**, loads user session CGI **123** into memory **160**, and executes the CGI. Upon authenticating the user, web server unloads user session CGI **123**, loads the CGI for the configuration menu from web applications **122** into memory **160**, and executes the configuration menu CGI. Upon completion of the configuration menu CGI, web server **115** unloads the configuration CGI and data output from the configuration menu CGI is

passed to the user via the user's web browser. In one embodiment, web server **115** may also be unloaded from memory like memory **160** until a communication is received from the user and while a CGI like the configuration menu CGI is being executed.

5 **[0021]** Web applications **122** may include firmware applications or CGIs such as a service processor setup menu to allow a user to set passwords and update machine firmware, a system power control menu to allow a user to control some aspects of how the machine powers on and the extent to which the boot sequence is completed, and a system information menu to provide the user with information about the boot sequence and errors, and a means of checking
10 and altering the availability of processor(s) **150** and memory **160**. In some embodiments, web applications **122** may be stored on a hard drive, in flash memory, in read only memory (ROM), or other non-volatile memory.

15 **[0022]** The privilege level associated with the user's login session may determine or limit the applications and/or functions of applications of web applications **122** that are available to the user to execute. For example, embedded system **110** may facilitate three types of users, an administrator, a customer, or a customer engineer and the applications and/or functions of applications of web applications **122** that are available to the user can depend upon the type of user associated with the user's login session. When the user logs in as an administrator, for
20 instance, the user may be able to add/remove customer logins as well as limit the availability of different customer logins locally and/or remotely.

25 **[0023]** Web applications **122** may include a user session CGI **123** to facilitate authenticating a user for embedded system **110**. More specifically, user session CGI **123** may include functions such as a user login **124**, a user session authenticator **125**, an arbitrator **126**, and a user login authenticator **130**. For example, the user executes web browser **185** on user computer **180** and enters the IP address to access embedded system **110**. In response to the connection, web server **115** loads and executes user session CGI **123**. User session CGI **123** may check for cookies received from the web browser **185**. When no cookies are received, user

session CGI **123** may initiate execution of user login **124**. On the other hand, when a cookie is received, user session CGI **123** may initiate execution of user session authenticator **125**.

[0024] User login **124** may facilitate display of a login window having prompts to obtain a name and a password from a user. Upon receiving the name and password, user login **124** may authenticate the name and password via user login authenticator **130**. When the user login is verified, user session CGI **123** generates a session ID to identify the user and the user's login session. The session ID may be a random number such as a 64-bit or 128-bit random number that is unique with respect session ID's generated for other login sessions. User session CGI **123** then bundles the session ID into a packet or the like to store in a user database in shared memory buffer **162**. User session CGI **123** also forwards the session ID to web browser **185** in the form of a cookie or the like such that the session ID can be returned to web server **115** when the user attempts to initiate another application of web applications **122**.

[0025] In some embodiments, the additional session information is bundled or associated with the session ID and stored in shared memory buffer **162** such as the IP address of user computer **180**, the user's privilege level, a time indication, and the like. In such embodiments, the additional session information may provide further verification of the user's identity.

[0026] User session authenticator **125** receives a session ID from the user and verifies that the session ID is a valid session ID, stored in shared memory buffer **162**, to authenticate the user for access to embedded system **120**. For example, after logging in to embedded system **110**, the applications of web applications **122** that are associated with the user's login session may terminate. Then, the user may attempt to initiate another application of web applications **122**. Web browser **185** returns the cookie having the session ID to web server **115**. Then, once the session ID is located in shared memory buffer **162**, the user is authenticated and the application that the user attempted to initiate is executed. In further embodiments, when the IP address for user computer **180** is stored with the session ID in shared memory buffer **162**, user session authenticator **125** may search shared memory buffer **162** for the session ID. Upon locating the session ID, user session authenticator **146** may compare the IP address of user computer **180**

with the IP address associated with the session ID in shared memory buffer **162** to confirm that these addresses are the same. When the IP addresses are the same, the user is authenticated. On the other hand, when, for instance, the user or another user attempts to forward a session ID from another IP address such as another computer, the authentication fails and the user is rejected or user login **124** is initiated to request that the user provide a name and password.

[0027] Arbitrator **126** arbitrates access to shared memory buffer **162**, or a portion thereof, based upon an indication in semaphore **164**. Before approving access to shared memory buffer **162** to compare a session ID with session IDs of authenticated users, arbitrator **126** checks semaphore **164** to determine whether another CGI is accessing the session IDs in shared memory buffer **162**. When semaphore **164** indicates that no other CGI, such as another copy of user session CGI **123** loaded into memory **160**, is accessing the session IDs in shared memory buffer **162**, arbitrator **126** stores one or more bits in semaphore **164** to prevent the session IDs of shared memory buffer **162** from simultaneous access by another CGI. When semaphore **164** indicates that shared memory buffer **162** is being accessed, arbitrator **126** prevents simultaneous access by another CGI. For example, two users may be accessing embedded system **110**. Each time one of the users communicates with embedded system **110**, a copy of user session CGI **123** is loaded into memory **160** and executed to verify the user's identity. While the session ID for the first user in shared memory buffer **162** is being accessed by one copy of user session CGI **123**, arbitrator **126** may lock the list of session IDs, referred to as a user database, in shared memory buffer **162** by storing an in-use indication in semaphore **164**. When a second copy of user session CGI **123** attempts to access the user database, arbitrator **126** checks semaphore **142** to determine whether an application is currently accessing shared memory buffer **140**, or a portion thereof. When arbitrator **126** determines that shared memory buffer **162** is being accessed, arbitrator **126** either places the request to access shared memory buffer **140** in a queue or rejects the request. In many embodiments, one copy of arbitrator **126** is loaded into memory **160** to arbitrate access to shared memory buffer **162** between multiple users.

[0028] In some embodiments, arbitrator **126** assigns and grants requests to access shared memory buffer **162** based upon one or more priorities associated with the privilege level of the

user, the timing of the request with respect to other requests, a priority assigned to the user's login session, or the like. For instance, when a customer engineer is logged in to maintenance or repair web server **110**, requests to access shared memory buffer **162** associated with the login session of the customer engineer may be given the highest priority, bypassing other requests that wait in a queue in their order of receipt. In other embodiments, arbitrator **126** may store high priority requests in a queue, servicing the requests in the queue and rejecting other requests until all the requests in the queue have been serviced. In further embodiments, arbitrator **126** may implement a round robin type arbitration scheme based upon the IP addresses of connected computers like user computer **180**.

[0029] User login authenticator **130** may be a CGI that includes algorithms to verify a user login for embedded system **110**. In particular, user login authenticator **130** may access a list of user names with corresponding passwords for customers and administrators in static **135**. Static **135** may be stored in non-volatile memory such as flash memory, electrically erasable, programmable memory (EEPROM), RAM, or the like and may maintain user names and passwords. Dynamic **134**, on the other hand, may be part of user login authenticator **130** and may include an algorithm that generates a unique password dependent upon, e.g., the date and/or time of the login, the serial number and the model number of the server including embedded system **110**, or the like. For example, a customer engineer may have to contact a manufacturer of the server, such as IBM, with the serial number and model number of the server to determine the password for a specific day. IBM implements an algorithm like the algorithm of dynamic **134**, to provide the customer engineer with the correct password so that the customer engineer's password can only authenticate the customer engineer on that day and/or time of day for access to embedded system **110**. In some embodiments, user login authenticator **130** and/or static **135** may also include additional information such as privilege levels, login session restrictions, IP addresses from which the user may log into embedded system **110**, an indication of a previous login session, and other data related to the login sessions by corresponding users.

[0030] Bus **140** may be one or more busses to facilitate communication between web server **115**, web applications **122**, processor(s) **150**, and memory **160**. In many embodiments,

bus **140** may comprise a combination of parallel and point-to-point, unidirectional and bidirectional busses and bridges.

[0031] Processor(s) **150** may include one or more processors like the IBM POWER4 or POWER4+ processors. In some embodiments, processor(s) **150** include Multichip Module (MCM) packaging and/or Single Chip Module (SCM) packaging. The SCM packaging may be mounted on a processor card and may include one or more processor cores. In some embodiments, one processor is dedicated for execution of applications associated with embedded system **110**. In other embodiments, one or more processors or threads of processor(s) **150** may execute instructions for applications associated with embedded system **110**.

[0032] Memory **160** represents memory built into the server including embedded system **110** and is shown as a single element for convenience. Memory **160** may include random access memory (RAM) such as double data rate (DDR) synchronous dynamic RAM (SDRAM), caches, buffers, read only memory (ROM); flash memory, and/or remote data storage like magnetic disk storage media, optical storage media, and flash memory drives. In the present embodiment, memory **160** includes memory for allocation to applications of web applications **122** when executed by embedded system **110**.

[0033] In the present embodiment, memory **160** also includes shared memory buffer **162**. Shared memory buffer **162** may be memory, e.g. 4 kilobytes (KB), allocated for use by embedded system **110** independent of allocations to individual applications, to store a list of session IDs. Unlike memory allocated for an application like a CGI, the data stored in shared memory buffer **162** is not de-allocated when a particular application terminates or unloads. For example, user login **124** may execute when a user first logs into embedded system **110**. The user enters a name and password in response to prompts from user login **124** and user login **124** stores the name and password in variables in memory **160**. The name and password are then compared with names and passwords by user login authenticator **130** to determine whether the user is authorized to log into embedded system **110**. When the user authorization is verified, a unique, session ID is generated and stored in shared memory buffer **162**. Then, user login **124** terminates

and the memory of memory **160** allocated to store the name and password is de-allocated and no longer accessible to applications. On the other hand, the session ID stored in shared memory buffer **162** remains accessible.

5 **[0034]** Shared memory buffer **162** may include semaphore **164**. Semaphore **164** may provide a flag having one or more bits of data to indicate whether one or more session IDs in shared memory buffer **162** are being accessed and/or modified. In several embodiments, a flag indicates that a list of session IDs, the user database, in shared memory buffer **162** is being accessed. In further embodiments, a flag is set for each session ID stored in shared memory
10 buffer **162** being accessed. Thus, session IDs other than the one being accessed or modified may be compared against a session ID received from web browser **185** to determine whether the session ID received is in the list of other session IDs. Then, when a flag in semaphore **164** is reset to indicate that the busy session ID is released and is no longer being accessed or modified, the session ID received from web browser **185** may be compared against the released session ID.

15 **[0035]** WAN/LAN **170** is a network connection to couple web server **110** with user computers such as user computer **180**. In some embodiments, WAN/LAN **170** may include a network in an office coupled via Ethernet, optical media like OptiConnect, or the like. In some embodiments, WAN/LAN **170** also couples with the Internet via a cable modem, a direct
20 subscriber line (DSL), a T1 line, a T3 line, or the like. In further embodiments, WAN/LAN **170** may include a network of temporary connections such as connections via a telephone system. In other embodiments, one or more user computers like user computer **180** may couple with embedded system **110** directly.

25 **[0036]** User computer **180** may include one or more computer systems such as personal computers, laptops, other servers, or the like, having hardware and software to communicate with embedded system **110** via WAN/LAN **170**. In particular, user computer **180** may include web browser **185** and cookies **190**. In other embodiments, user computer **180** may include applications that operate in a manner similar to web browser **185**, such as a text interface
30 application for a terminal, a PDA, or the like. Web browser **185** includes software adapted to

provide a GUI that, in many embodiments, can be customized based upon a user's preferences with regards to command structures, text sizes, fonts, colors, sounds, languages, and etc. Web browser **185** accepts cookies like cookies **190** to store information related to a web site, or a session ID for embedded system **110** and returns the cookie to web server **115** when requesting that an application such as an application of web applications **122** be initiated. Web browser **185** may include Microsoft's Internet Explorer, AOL's Netscape Navigator, or the like.

[0037] Cookies **190** may include a session ID stored in temporary memory such as memory allocated for web browser **185** or a more permanent memory such as a file stored on a hard drive of user computer **180**. After a user logs into embedded system **120**, and the session ID is generated to identify the user and the login session, for example, the session ID may be transmitted to web browser **185** in the form of a cookie and stored in cookies **190**.

[0038] Referring now to FIG 2, there is shown an embodiment of an apparatus **200** to authenticate a user. Apparatus **200** may log a successful user authentication for a server. In particular, apparatus **200** may generate a session ID in response to an indication that the user's login has been authenticated **205** and store the session ID in a shared memory buffer **250** so the user can be subsequently authenticated without, e.g., requesting that the user re-enter a user name and password. Apparatus **200** includes a session creator **210**, shared memory buffer **250**, a database arbitrator **260**, and a session authenticator **280**.

[0039] Session creator **210** may couple with shared memory buffer **250** to generate a unique, session ID in response to user authentication **205** to identify a login session for a user, store the unique, session ID in a memory location, and transmit the unique, session ID to the user. For example, a user may initiate access to a system such as an embedded system associated with a service processor of the server to modify system configuration preferences. When the user is accessing the system for the first time, or when the user's previous login session has expired, the user is prompted to provide login information. Upon verifying that the user is authorized to access the system, a session creator **210** may be initiated to assign the user a unique

session ID so user session authenticator **280** can authenticate the user without requesting the user to provide login information again.

[0040] Session creator **210** may include a session ID generator **220**, a bundle generator **230**, a bundle storer **240**, and a bundle transmitter **245**. Session ID generator **220** generates a unique, session ID in response to the user authentication **205** to identify a login session for a user. The unique, session ID may be unpredictable such that a user cannot guess the unique, session ID that will be created for that user or for any other user. In some embodiments, session ID generator **220** includes a random number generator **222** to generate a random number for the session ID to associate with the user and the login session. For instance, after a successful login, random number generator **222** may generate a 64-bit, random number. In several of these embodiments, session ID generator **220** may append or generate a session ID based upon, e.g., an indication of the date and time of the user's login and/or the user's IP address to ensure that the session ID is unique.

[0041] Session ID generator **220** includes a uniqueness verifier **224** to verify that the random number generated for the user has not been previously assigned. In particular, upon generating a random number for the session ID, uniqueness verifier **224** may couple with shared memory buffer **250** to compare the random number with session ID's previously assigned. When the random number is the same as a random number previously assigned as a session ID, random number generator may generate a different random number to assign to the user for the login session.

[0042] Bundle generator **230** may bundle the unique, session ID with additional session information, associating the additional session information with the user's login session. For example, bundle generator **230** may associate a session ID with session information such as the user's IP address, privilege level, location, Internet service provider, user name, and etc. In some embodiments, bundle generator **230** also includes a time stamper **235**. Time stamper **235** may associate a time indication with the unique, session ID to facilitate expiring the unique, session ID after a selected time period. In many of these embodiments, the time period may be

measured from the most recent user activity. For example, the session ID may expire if the user remains inactive for an hour. In further embodiments, the session ID may expire within 5 hours of the initial login for the corresponding login session.

5 [0043] Bundle storer **240** may store the session ID in a user database **254** of shared memory buffer **250**. More specifically, bundle storer **240** may packetize the session ID and associated additional session information, and request access to shared memory buffer **250** from database arbitrator **260** to store the packet in an available entry of user database **254**.

10 [0044] Bundle transmitter **245** may transmit a bundle having the unique session ID to a web browser. For instance, after a user logs into the server via a web browser, bundle transmitter may return a cookie with the session ID to the web browser. In some embodiments, the cookie also contains additional data such as an indication describing the expiration of the cookie such as five hours. In further embodiments, no expiration is included in the cookie and the browser
15 assigns a default expiration.

[0045] Shared memory buffer **250** includes memory configured to retain the session ID independent of de-allocations of memory for individual applications and, thus, independent of the termination of applications executed on the server. In particular, shared memory buffer **250**
20 may include one or more memory locations in a buffer, RAM, cache, and the like, that are not allocated to a specific application like a login application. For example, after the user logs into the server, the login application may terminate and no other applications may be running. Shared memory buffer **250**, however, is not de-allocated upon unloading the login application or other applications associated with the server from memory so the session IDs in user database
25 **254** remain available for subsequently initiated applications. In many embodiments, the contents of shared memory buffer **250** are lost when the server re-boots but in one embodiment, the session IDs of user database **254** remain available even after the server re-boots. In several embodiments, the session IDs of user database **254** remain available until they are removed.

[0046] Shared memory buffer includes semaphore **252** and user database **254**. Semaphore **252** includes one or more flags to indicate when user database **254**, and/or an entry thereof, is being accessed and/or modified. User database **254** includes a session ID list **256** and, in several embodiments, additional session information associated with one or more session IDs in session ID list **256**. Session ID list **256** may include session ID's associated with unexpired user login sessions. In further embodiments, session ID list **256** may retain a list of expired session ID's associated with an indication that the session ID's have expired. One embodiment employs a data encryption scheme for user database **254** like a public/private key data encryption scheme to allow authorized applications to access the session IDs while protecting the session IDs from unauthorized access.

[0047] Database arbitrator **260** may prevent simultaneous access of content of user database **254**, or an entry therein, by more than one of the applications executed on the server. In many embodiments, database arbitrator **260** locks user database **254** when granting access to one application and removes the lock upon completion of the access. If a subsequent request to access user database **254** is made while user database **254** is locked, database arbitrator **260** denies that access. For example, bundle storer **240** generates a packet having a session ID to store in user database **254** and requests access to user database **254** via database arbitrator **260** to store the packet. When semaphore **252** indicates that user database **254** is in use, database arbitrator **260** may delay storage of the packet until semaphore **252** indicates that user database **254** is no longer being accessed. On the other hand, when semaphore **252** indicates that user database **254** is not being accessed, database arbitrator **260** stores an indication or sets a flag in semaphore **252** to indicate that user database is in use and grants access in response to the request to store the packet. In embodiments wherein separate indications in semaphore **252** describe whether entries of user database **254** are in use, database arbitrator **260** may prevent session authenticator **280** or other applications from accessing an entry that is in use, but bundle storer **240** may store packets in available entries without first requesting access via database arbitrator **260**.

[0048] Session authenticator **280** may couple with shared memory buffer **250** to authenticate the user for an application of the applications executed on the server in response to receipt of the unique, session ID upon verifying that the unique, session ID is stored in shared memory buffer **250**. In some embodiments, session authenticator **280** also verifies additional session information. For instance, after a user logs in and attempts to initiate a subsequent application associated with the login session, the web browser utilized by the user returns a cookie having a session ID. The IP address of the user may also be determined from the communication so after the session ID received from the web browser is determined to be stored in user database **254**, the IP address of the communication from the web browser may be compared with the IP address associated with the session ID in user database **254**. When the IP addresses are the same, the user is authenticated. On the other hand, when IP addresses are different, the user may not be authenticated.

[0049] Session authenticator **280** includes a bundle receiver **282**, a session ID comparator **284**, and a time monitor **290**. Bundle receiver **282** may receive a cookie or the like from a user's web browser to authenticate the user and the user's login session. In particular, bundle receiver **282** may recognize a cookie attached to a communication such as a communication from the user requesting that a CGI for a system configuration menu be initiated, extract a session ID from the cookie, and initiate session ID comparator **284** to determine whether the session ID authenticates the user for a login session.

[0050] Session ID comparator **284** may compare the unique, session ID received from the user with session IDs previously stored user database **254**. In some embodiments, when the number of session IDs is expected to be small such as a dozen or less, the unique, session ID is compared with session IDs in session ID list **256** in a linear manner, e.g., each session ID in session ID list **256** in order from the first to the last. In other embodiments, when the number of session IDs is expected to become large, e.g., hundreds, user database search **286** may be implemented to perform a binary search of the session IDs in session ID list **256**. In such embodiments, the session IDs may be maintained in an order and the binary search may compare the session ID extracted from the cookie to a session ID substantially in the middle of session ID

list **256**. Then, depending upon whether the session ID extracted from the cookie is larger or smaller, compared to the middle of the remaining half of session IDs in session ID list **256**, and so on. In further embodiments, other search methods may be implemented including index searches and the like. In an alternative embodiment, when the record number of the session ID is also extracted from the cookie, session ID comparator **284** may compare the extracted session ID to the session ID having the corresponding record number only.

[0051] In many embodiments, after session ID comparator **284** compares a session ID from a cookie against session IDs in user database **254** and finds a match, time monitor **290** may update the time indication or time stamp associated with the matching session ID in user database **254**. However, if the matching session ID in user database **254** is expired, the user's identity may not be verified via the session ID from the cookie and time monitor **290** may remove the matching session ID from user database **254** or invalidate the matching session ID. In further embodiments, while session ID comparator **284** compares a session ID from a cookie against session IDs in user database **254**, time monitor **290** may compare time stamps associated with session IDs against the session ID from the cookie to determine whether the corresponding session IDs have expired. Any session ID determined to be expired by time monitor **290** is either removed from user database **254** or invalidated.

[0052] In further embodiments, time monitor **290** may facilitate monitoring time stamps or indications in user database **254** with an independent search from comparisons made by session ID comparator **284**, in addition to or as an alternative for monitoring time stamps in conjunction with session ID comparator **284**. For instance, time monitor **290** may couple with shared memory buffer **250** to periodically search for and remove expired session IDs from user database **254** such as session IDs that expired after a period of inactivity by the user, a period of time from the initial login by the user, a period of time since entering the session ID into session ID list **256**, or the like.

[0053] Alternative embodiments may be designed to interface with applications like web browsers that facilitate storage of session IDs on a user's computer or terminal and the return of

the session ID with communications such as a text terminal with a text interface rather than a GUI interface, a PDA with a limited text or GUI interface, or the like.

[0054] FIG 3 depicts an example flow chart 300 of a method to authenticate a user for interaction with applications on a server. Flow chart 300 begins with element 310, initiating a CGI to authenticate a user for interaction with a web server application. When a cookie does not accompany the request from the web browser, a login application may request that the user provide login information such as the user's name and password. The login information is verified (element 314) with user login data on the server.

[0055] Upon verifying that the user is authorized to access the server, a unique, session ID is generated (element 316) to associate with the user's login session. The session ID may include a unique, random number such as a 512-bit, random number. In some embodiments, generating a unique, random number includes comparing the random number to other session IDs stored in the user database of a shared memory buffer to verify that the random number is unique. For example, a random number for the user's login session may be generated. Then, the user database may be locked via a semaphore to prevent other applications from simultaneously accessing the user database while the random number is compared to session IDs stored in the user database. If the random number is unique with respect to the list of session IDs in the user database, the random number is associated with the user's login session.

[0056] In element 318, a packet is generated for the unique, session ID to store in the user database. The packet may include the unique, session ID and may also include other information that describes the context of the user's login session. For example, the user may log into the server via a computer identified by an IP address. The IP address for the user's computer is associated with the session ID assigned to the user's login session such that IP addresses of subsequent transmissions from the user can be compared the IP address associated with the user's ID in the user database. In further embodiments, the packet having the session ID is encrypted to prevent or substantially attenuate unauthorized access to the session ID.

[0057] The user database is locked in element **320** to prevent simultaneous access of the user database by more than one application while the packet is stored in the user database. In other embodiments, an entry in which the packet is to be stored is locked to prevent simultaneous access to the entry.

5

[0058] Upon locking the user database, the packet is transmitted to the shared memory buffer for storage in the user database in element **322**. The shared memory buffer retains the packet for access even after termination of the web applications and the web server currently running. In many embodiments, the shared memory buffer is allocated as an independent allocation from allocations of memory to an individual application. Thus, when the web server and/or another application is executed in response to a communication from a user, the packet may be accessed by one or more applications. Once the packet is stored, the user database is unlocked to facilitate access by other applications in element **324**. For example, a flag or bit may be set to a logical one to indicate that the user database is being modified or accessed. Then, when another application attempts to access the user database while the packet is being stored, until the flag or bit is set to a logical zero.

10

15

[0059] In element **326**, a cookie having the unique, session ID is generated for transmission to the user's web browser. After the cookie is forwarded to the web browser in element **328**, the cookie may be returned to the server when the user attempts to initiate another application associated with the user's login session. In some embodiments, the cookie may be encrypted prior to transmission.

20

[0060] In element **312**, when the cookie is returned to the server, the user may avoid re-entry of login information. In particular, receipt of the cookie having a session ID from the user's web browser (element **330**) may identify the user's login session and authenticate the user. The session ID is extracted from the cookie (element **332**) and the user database is locked (element **334**) to facilitate access to the user database to compare the extracted session ID with session IDs for authenticated users. In several embodiments, extracting the session ID from the cookie may involve decrypting the session ID.

25

30

[0061] Upon determining the session ID embedded in the cookie, the session ID from the cookie is compared with a selected session ID from the user database in element 336. A session ID may be selected from the user database by, selecting the first session ID, the last session ID, a session ID substantially in the middle of the user database, a session ID corresponding to a record number or memory address also embedded in the cookie, or the like. When the session ID extracted from the cookie does not match the selected session ID (element 338) and more session IDs are stored in the user database (element 342), another session ID is selected from the user database and compared with the session ID extracted from the cookie (element 336). Once a matching session ID is found (element 338), the user is authenticated in element 340 and the user database is unlocked (element 346) to allow subsequent accesses.

[0062] On the other hand, when no session IDs in the user database are found to match the session ID extracted from the cookie (element 342), the user's request to initiate an application associated with the user's login session is rejected or the login application is initiated to authenticate the user based upon entry of login information (element 344) such as a user name and password. The user database is then unlocked (element 346) to facilitate access to the user database by other applications.

[0063] FIG 4 depicts an example flow chart 400 of functionality for a method like flow chart 300 in FIG 3 for removing user sessions upon expiration or in response to a user activity such as logging out of a session. Such functionality is advantageous since the allocation of memory to a shared memory buffer for the user database may be independent of de-allocations of memory for individual applications and the entries in the shared memory buffer may remain in the shared memory buffer indefinitely or until the operating system that made the allocation of memory for the shared memory buffer is terminated and/or the computer containing the shared memory buffer is turned off or powered down. Flow chart 400 begins with monitoring for user activity in element 410. When the user logs into the server, a user session is initiated and a time indication may be initially stored with a session ID in the user database to indicate the first user activity. After the initial login, the user's activity may be monitored or applications initiated by

the user may report user activity. For example, receipt of a request from any user may initiate the elements of flow chart **400**. On the other hand, applications operating on the server may periodically or at specified points of execution, initiate the elements of flow chart **400**.

5 **[0064]** When user activity (element **410**) has occurred and involves the user indicating a desire to logout of the server (element **425**), the user database is locked, and the user's unique, session ID is removed from the user database to prevent subsequent authentication of a user based upon the unique, session ID (element **440**). Then, the user database is unlocked (element **445**).

10 **[0065]** When user activity (element **410**) has occurred and does not involve the user indicating a desire to logout of the server (element **425**), a new time indication may be stored in the user database (element **430**) to indicate the time and/or date of the user activity, extending the expiration of the user's login session. While accessing the user database, time indications for
15 other session IDs may be checked (element **435**) to see if the corresponding login sessions have expired. If login sessions associated with session IDs in the user database have expired, the corresponding session IDs are removed from the user database (element **440**) to prevent future access to the server based upon those session IDs. Then, the user database is unlocked in element **445**.

20 **[0066]** When elements of flow chart **400** are initiated without a corresponding user activity (element **410**), such as period implementation of a time monitoring CGI by the server, the user database is locked in element **415** and the user database is accessed to determine whether time indications associated with session IDs correspond to expired login sessions
25 (element **435**). When login sessions have expired, the corresponding session IDs are removed from the user database (element **440**) and the user database is unlocked (element **445**) to allow subsequent access by applications on the server.

30 **[0067]** One embodiment of the invention is implemented as a program product for use with a computer system such as, for example, the system **100** shown in FIG 1. The program(s)

of the program product defines functions of the embodiments (including the methods described herein) and can be contained on a variety of signal-bearing media. Illustrative signal-bearing media include, but are not limited to: (i) information permanently stored on non-writable storage media (e.g., read-only memory devices within a computer such as CD-ROM disks readable by a CD-ROM drive); (ii) alterable information stored on writable storage media (e.g., floppy disks within a diskette drive or hard-disk drive); and (iii) information conveyed to a computer by a communications medium, such as through a computer or telephone network, including wireless communications. The latter embodiment specifically includes information downloaded from the Internet and other networks. Such signal-bearing media, when carrying computer-readable instructions that direct the functions of the present invention, represent embodiments of the present invention.

[0068] In general, the routines executed to implement the embodiments of the invention, may be part of an operating system or a specific application, component, program, module, object, or sequence of instructions. The computer program of the present invention typically is comprised of a multitude of instructions that will be translated by the native computer into a machine-readable format and hence executable instructions. Also, programs are comprised of variables and data structures that either reside locally to the program or are found in memory or on storage devices. In addition, various programs described hereinafter may be identified based upon the application for which they are implemented in a specific embodiment of the invention. However, it should be appreciated that any particular program nomenclature that follows is used merely for convenience, and thus the invention should not be limited to use solely in any specific application identified and/or implied by such nomenclature.

[0069] It will be apparent to those skilled in the art having the benefit of this disclosure that the present invention contemplates methods, systems, and media to authenticate a user by assigning a unique, session ID to a login session and maintaining the session ID in memory that is not de-allocated in response to the termination of an application on the server. It is understood that the form of the invention shown and described in the detailed description and the drawings

are to be taken merely as examples. It is intended that the following claims be interpreted broadly to embrace all the variations of the example embodiments disclosed.